

TALA OFFSHORE AS

WELDED PIPE IN SIZES ACCORDING TO ASTM/ASME



Pipe is supplied annealed and pickled in random lengths or cut to fixed lengths in steel grades ASTM 304/304L and 316/316L. Welded pipes are either 100% Eddy Current tested or hydrostatic and expansion tested.

Pipes stocked according to ASTM A312/ASME SA 312, ASTM A999/M
Tolerances according to ASME B36.19
OD = outside diameter, WT = wall thickness

OD mm	WT mm	in.	Sch	Weight Kg/m
21,34	2,11	1/2"	10S	1,02
21,34	2,77	1/2"	40S	1,29
26.67	2.11	3/4"	10S	1,3
26.67	2.87	3/4"	40S	1,71
33.40	1.65	1"	5S	1.31
33.40	2.77	1"	10S	2.13
33,40	3.38	1"	40S	5.54
42,16	1.65	1 1/4"	5S	1.67
42,16	2,77	1 1/4"	10S	2,73
42,16	3,56	1 1/4"	40S	3,44
48.26	1.65	1 1/2"	5S	1.92
48,26	2,77	1 1/2"	10S	3.16
48,26	3,68	1 1/2"	40S	4.11
60.33	1.65	2"	5S	2.42
60,33	2,77	2"	10S	3.99
60,33	3,91	2"	40S	5.52

Mailing address:
Tala Offshore AS
Kjelsbergalle 2, 4050 Sola

Visiting address:
Kongshaugvegen 21
4050 Sola

Phone: +47 979 84 841
e-mail: info@talaoffshore.no
www.talaoffshore.no
Org no. 917 689 652

TALA OFFSHORE AS

OD mm	WT mm	in.	Sch	Weight Kg/m
73,03	3,05	2 1/2"	10S	5,35
73,03	5,16	2 1/2"	40S	8,77
88,90	5,49	3"	5S	4,58
88,90	3,05	3"	10S	6,56
88,90	5,49	3"	40S	11,47
101,60	3,05	3 1/2"	10S	7,53
114,30	2,11	4"	5S	5,93
114,30	3,05	4"	10S	8,50
114,30	6,02	4"	40S	16,32
141,30	3,40	5"	10S	11,60
141,30	6,55	5"	40S	22,10
168,30	2,77	6"	5S	11,48
168,30	3,4	6"	10S	14,04
168,30	7,11	6"	40S	28,69
219,10	3,77	8"	5S	15,00
219,08	3,76	8"	10S	20,00
219,08	8,18	8"	40S	43,20
273,00	3,40	10"	5S	22,95
273,05	4,19	10"	10S	27,80
273,05	9,27	10"	40S	60,30
323,90	3,96	12"	5S	31,72
323,90	4,57	12"	10S	36,54
323,90	9,53	12"	40S	75,02
355,60	4,78	14"	10S	41,99
355,60	9,53	14"	STD	82,58
406,40	9,53	16"	STD	94,71
406,40	4,78	16"	10S	48,07
457,20	4,78	18"	10S	54,15
508,00	5,54	20"	10S	69,70
610,00	6,35	*24"	10S	98,92

*24" is produced with two seams